





PRODUCT DATA SHEET

Product code 3002923
EAN code 8712879149682
Product description LSC Candle B35 Softline Straight filament 220-240V 6W 600lm 2900K E14 dimmable via LED dimmer

Type of light source

Lighting technology used	LED	Non-directional or directional	NDLS
Mains or non-mains	MLS	Connected light source (CLS)	No
Colour tuneable light source (CTLS)	No	Envelope	No
High luminance light source	No	Dimmable	dimmable via LED dimmer
Anti-glare shield	No	Lamp holder fitting type/size	E14

General product parameters

Energy consumption in on-mode	6 kWh/1000h	Energy efficiency class	F
Useful luminous flux (Φ_{use})	600 lm	Measured in	sphere (360°)
Colour temperature (CCT)	2900 K	Declared lifetime (L _{70B50})	15000 Hr
On-mode power (P _{on})	6 W	Standby power (P _{sb})	0 W
Network standby power (P _{net})	0 W	Colour rendering index (CRI)	95
Claim of equivalent power	Yes	Equivalent power (W)	47 W
Voltage (V)	220-240 V	Frequency (Hz)	50/60 Hz
Chromaticity coordinate x	0.436	Chromaticity coordinate y	0.399
Product height	98 mm	Spectrum	
Product length	-	(For complete report scan EPREL QR code)	
Product width	-		

Product parameters for LED & OLED light sources

R9 colour rendering index value	81	Survival factor	-
Lumen maintenance factor	0.93	Colour consistency in MacAdam ellipse (SDCM)	<= 6 steps MacAdam ellipse
Displacement factor (cos ϕ 1)	0.5		
LED light source replaces a fluorescent light source	Not applicable		
Flicker metric (P _{st} LM)	1	Stroboscopic effect metric (SVM)	0.4