





## PRODUCT DATA SHEET

**Product code** 3006445  
**EAN code** 8712879155218  
**Product description** LSC GLS A60 Softline RA95 Straight filament 220-240V 12W 1521lm 4000K E27 dimmable via LED dimmer

### Type of light source

Lighting technology used	LED	Non-directional or directional	NDLS
Mains or non-mains	MLS	Connected light source (CLS)	No
Colour tuneable light source (CTLS)	No	Envelope	No
High luminance light source	No	Dimmable	dimmable via LED dimmer
Anti-glare shield	No	Lamp holder fitting type/size	E27

### General product parameters

Energy consumption in on-mode	12 kWh/1000h	Energy efficiency class	E
Useful luminous flux ( $\Phi_{use}$ )	1521 lm	Measured in	sphere (360°)
Colour temperature (CCT)	4000 K	Declared lifetime ( $L_{70B50}$ )	15000 Hr
On-mode power ( $P_{on}$ )	12 W	Standby power ( $P_{sb}$ )	0 W
Network standby power ( $P_{net}$ )	0 W	Colour rendering index (CRI)	95
Claim of equivalent power	Yes	Equivalent power (W)	100 W
Voltage (V)	220-240 V	Frequency (Hz)	50/60 Hz
Chromaticity coordinate x	0.3818	Chromaticity coordinate y	0.3797
Product height	105 mm	Spectrum	
Product length	-	(For complete report scan EPREL QR code)	
Product width	-		

### Product parameters for LED & OLED light sources

R9 colour rendering index value	80	Survival factor	-
Lumen maintenance factor	0.93	Colour consistency in MacAdam ellipse (SDCM)	<= 6 steps MacAdam ellipse
Displacement factor ( $\cos \phi_1$ )	0.7		
LED light source replaces a fluorescent light source	Not applicable		
Flicker metric ( $P_{st LM}$ )	1	Stroboscopic effect metric (SVM)	0.9